



Xtra chalao, Xtra kamao!

20% Xtra

xtra

- Long Deck
- Long Wheel Base
- Strong Platform
- Gear Box Performance
- Long Clutch Life
- Engine Oil Life

Yani xtra Profit



also available in BSIII

apé[®] xtra LD

For details SMS ape3 to 56677

TOLL FREE HELPLINE
1800-121-0007



Maximum mileage



World class customer care



Highest loadability



Lowest operating cost

Maximum Mileage • Lowest Operating Cost • Highest Loadability • World Class Customer Service



Xtra Long Deck

Length increased by 180 mm, making it best in class. This means extra space, extra volume and extra profit per trip.




Xtra Long Wheel Base

Longest wheel base in its category - 2100 mm, which guarantees extra stability



Xtra Strong Platform

Cold rolled loading tray with additional reinforcement, which enhances strength, resulting in better life of loading tray



Xtra Reliable Gearbox

New extra robust gearbox gives you extra performance & reliability.



Xtra Engine-Oil Life

New special oil - "ape life" provides 10,000 km of drain period, which reduces maintenance cost by 50%.



Xtra Aesthetics

Sleek & smart console, designed for visual appeal and convenience. Extra long seat for driver's comfort.



Xtra Long Clutch Life

Upgraded clutch that withstands extra torque, enhances clutch life & saves on maintenance cost.



Xtra Profits

With improved features that reduce maintenance cost and maintains the high performance standard of the vehicle; ape xtra LD is designed to deliver on every aspect - including extra profits.

• Also available in Hi-Body & Pickup versions • Also available in CNG & LPG fuel variants

apé[®] xtra LD

also available in BSIII

UNIQUE
20
MONTHS
EXTENDED WARRANTY



Piaggio Vehicles Pvt. Ltd. 102, Phoenix, Bund Garden Road, Pune - 411001.
Tel: 91-20-66013150. Fax: 91-20-66013157.

Technical Specifications

Engine

Type

Single Cylinder, 4 stroke, Direct Injection

No. of cylinders

One

Displacement

395 cc

Maximum Power, kW@rpm

7.38 bhp @ 3600 rpm

Maximum Torque, Nm @rpm

16.7 N.m @ 2500 rpm

Compression Ratio

18 : 1 [± 0.5%]

BSIII Engine

Type

Single Cylinder, Naturally Aspirated Air Cooled

No. of cylinders

One

Displacement

436 cc

Maximum Power, kW@rpm

5.52 kW @ 3600 rpm ± 50 rpm

Maximum Torque, Nm @rpm

18 Nm @ 2400-2200 rpm

Compression Ratio

19 : 1 [± 0.5%]

Clutch Type

Multi Disc, Wet type

Gear Box

Constant Mesh G.B. with 4 Forward + 1 Reverse

Suspension

Front

Helical spring with Hydraulic telescopic Shock absorber

Rear

Rubber compression spring with Hydraulic telescopic Shock absorber

Steering

Handle Bar Type

Brakes

Drum brakes hydraulically actuated internal expanding shoe type

Tyres

Tyre Size

4.50-10, 8PR

Tyre Type

Cross/Tube

Electrical System

System voltage, V

12DC

Battery rating, Ah

50 Ah

Wiping System

Electrically Operated

Fuel tank capacity

10.5 Ltr

Dimensions (in mm)

Wheel base, mm

2100

Overall width, mm

1490

Overall length, mm

3145

Overall height, mm

1635

Rear track, mm

1260

Min. ground clearance, mm

240

Load Body Platform Area, mm

1660 L x 1400 W

Weight

Maximum GVW, kg

975

Kerb weight, kg

438

Payload, Kg

537

Special add-on accessories: Bottle holder and mobile charger socket.
First time in India - Automatic Windshield Washer.
Specifications are subject to improvement / change.